

NEO Series (active)

Self-powered loudspeakers



Rear View

The self powered **NEO A series** complete the **NEO series** for maximum convenience and flexibility.

All models feature a two channel class D amplifier, with bass and treble tone controls, RCA, 3.5 mm mini-jack inputs and a powered output for a passive speaker (included).

Each **NEO A series** model is supplied as a complete pair: a self-powered loudspeaker with matching a passive loudspeaker, mains cable and 3m speaker link cable.

Installers can choose a black or white finish, using these loudspeakers as another element of the interior decor.


Their metal wallmount provide a secure fixation, moving the loudspeaker in pan and tilt axes.

Features



- Loudspeakers designed for fixed installations
- Set composed of one active loudspeaker and another passive loudspeaker.
- Volume and tone controls (Bass/Treble)
- Unbalanced input and stereo input
- Available in two colours: (black and white)
- Elegant design
- Aluminium grille for a long lifetime
- Metal wall-mount bracket with fast mounting system.
- Mounting bracket enables pan and tilt

Dimensions

* In mm.



NEO 5A
NEO 6A
NEO 8A



	NEO 5A	NEO 6A	NEO 8A
A	166 mm	175 mm	240 mm
B	244 mm	290 mm	370 mm
C	171 mm	200 mm	260 mm
D	210 mm	267 mm	333 mm
E	153 mm	167 mm	218 mm

NEO Series (active)

Rear View




Specifications

Model:	NEO 5A	NEO 6A	NEO 8A
Elements:	5" Woofer + 0.5" Tweeter	6.5" Woofer + 1" Tweeter	8" Woofer + 1" Tweeter
Power Output:	2x 25W RMS	2x 30W RMS	2x 40W RMS
Frequency response:	60 Hz - 20 kHz	55 Hz - 20 kHz	50 Hz - 20 kHz
Sensitivity:	1V / 2,21 dBu	1V / 2,21 dBu	1V / 2,21 dBu
Dispersion (H xV):	90° x 80°	100° x 80°	100° x 80°
Material (enclosure):	ABS plastic	ABS plastic	ABS plastic
Material (grille):	Aluminium	Aluminium	Aluminium
IP rating:	IP 45	IP 45	IP 45
Input connection:	2x RCA unbalanced + 1x mini-jack 3.5 mm stereo	2x RCA unbalanced + 1x mini-jack 3.5 mm stereo	2x RCA unbalanced + 1x mini-jack 3.5 mm stereo
Output connection:	2 pin Terminal Euroblock (to passive loudspeaker)	2 pin Terminal Euroblock (to passive loudspeaker)	2 pin Terminal Euroblock (to passive loudspeaker)
Finished colour:	RAL 9003 (W) / RAL 9004 (B)	RAL 9003 (W) / RAL 9004 (B)	RAL 9003 (W) / RAL 9004 (B)
Main supply:	AC 115/230V, 50/60 Hz	AC 115/230V, 50/60 Hz	AC 115/230V, 50/60 Hz
Dimensions:	171 x 244 x 166 mm	200 x 290 x 175 mm	240 x 370 x 260 mm
Weight:	4,4 kg	5,1 kg	5,46 kg

* Specifications are subject to change without notice.

Accessories



NEO 5A/6A/8A
Metal wall-mount
bracket
(included)



Each set is composed by one active model and another passive model.



Rev. 12.06.01